

Reference

Glass Architecture PR60



University of Music and Performing Arts, Munich

Essential info

Place / Country:	Munich, Germany
Year:	2009
Project:	Administrative building
Solutions:	Glass Roof KWS 60 Ventilation Flap PR60 Electric motor openers Solar control insulating glass
Effizienz:	61% Energieeinsparung $U_w=1,2 \text{ W/(m}^2\text{K)}$ vs. $U_w=3,1 \text{ W/(m}^2\text{K)}$ nach EnEV 2009

Glass roofs reconditioned in the south and north section of the building while taking into account current energy efficiency requirements for daylight systems. The steel bearing structures continue to be used as the supporting structure due to building preservation reasons.

- Glass roofs in hipped roof shape with 20° pitch, U_g value = 1.1 W/(m²K)
- Flap systems for SHEV function and natural ventilation; light transmission tested to EN 12207 (Class 4), watertightness as per EN 12208 (Class E1200), resistance under wind load as per EN 12210 (Class C4/B5)
- Thermally separated, extruded aluminium sections
- Installation of supply cable and flap control connection to building control system
- Heat protection insulation glazing made of laminated safety glass, 67% light transmittance and 46% overall energy transmission, Thermix edge bond, sound reduction index R_{wp} about 35 dB

LAMILUX HEINRICH STRUNZ GMBH

POB 1540 - 95105 Rehau/Germany - Phone: +49 (0)9283/595-0 - Fax: +49 (0)9283/595-290

E-Mail: information@lamilux.com - www.lamilux.com

Reference

Glass Architecture PR60



University of Music and Performing Arts, Munich



LAMILUX HEINRICH STRUNZ GMBH

POB 1540 - 95105 Rehau/Germany - Phone: +49 (0)9283/595-0 - Fax: +49 (0)9283/595-290

E-Mail: information@lamilux.com - www.lamilux.com